



Overhaul Balls

UB500 Top Swiveling Overhaul Ball

S320 or S320N
Eye Hook



S316A SHUR-LOC®
Eye Hook




- The top swiveled design on the UB500 assures the ball remains stationary if the wire line spins.
- The swivel incorporates a sealed roller thrust bearing together with a grease fitting for easy lubrication.
- Each ball can be equipped with the new McKissick US422T Wedge Socket which can be easily adjusted to fit various sizes of wire rope by changing the wedge (Ensure that correct wedge is used for selected wire rope size).
- Design Factor 4:1.
- All hooks used on UB500 Overhaul Balls (S320, S320N & S1316A) are forged from alloy steel. The S320 and S320N hooks come complete with latches.
- Sizes 4 tons through 10 tons available with Crosby's S1316A "Positive Locking" SHUR-LOC® hook which may be used for lifting personnel. Meets OSHA Rule 1926.550(g).
- The S320 hook (PL latch) and the S320N hook (S4320 latch), with the proper latch attached, may be used for personnel lifting when secured with proper device (Bolt, nut and pin for the PL latch; Cotter pin for the S4320 latch). Meets OSHA Rule 1926.550 (g).

Overhaul Ball Assembly					Optional US-422T / US 422 Wedge Sockets					
McKissick UB500 Model No.	UB500 "E" Eye Hook Stock No.	UB500 "S" SHUR-LOC Stock No.	Working Load Limit (tons)	Weight Each (lbs.)	Wire Rope Size (in.)	Model No.	Wedge Socket Assy Stock No.	Weight Each (lbs.)	Wedge Only Stock No.	Weight Each (lbs.)
MB4T35	1036000*	1036005	4	58	3/8	US4T	1044300	4.6	1047310	0.6
MB4T85	1036009*	1036018	4	102	7/16	US4T	1044309	4.6	1047301	0.6
MB4T150	1036027*	1036032	4	162	1/2	US4T	1044318	4.6	1047329	0.6
MB4T200	1036036*	1036041	4	201	1/2	US5T	1044327	8.5	1047338	1.0
MB7T85	1036045*	1036050	7	109	9/16	US5T	1044336	8.5	1047347	1.0
MB7T150	1036054*	1036063	7	170	5/8	US5T	1044345	8.5	1047356	1.0
MB7T200	1036072*	1036077	7	210	5/8	US6T	1044354	9.4	1047365	1.4
MB7T285	1036081*	1036086	7	321	3/4	US6T	1044363	9.4	1047374	1.4
MB10T150	1036090*	1036095	10	216						
MB10T200	1036099*	1036108	10	260						
MB10T285	1036117*	1036122	10	365	5/8	US6T	1044354	9.4	1047365	1.4
MB10T350	1036126*	1036131	10	403	3/4	US6T	1044363	9.4	1047374	1.4
MB10T650	1036135*	1036140	10	748	7/8	US8T	1044404	20.8	1047425	7.6
MB12T150	1036144*	-	12	216	1	US8T	1044417	20.8	1047431	8.6
MB12T200	1036153	-	12	258	1-1/8	US10T	1044426	46.5	1047440	12.5
MB12T285	1036171*	-	12	365	1-1/4	US10T	1044435	46.5	1047459	15.0
MB12T350	1036180*	-	12	403						
MB12T650	1036189*	-	12	718						
MB15T200	1036198*	-	15	298						
MB15T350	1036207*	-	15	456						
MB15T650	1036216*	-	15	753						
MB15T1150	1036225*	-	15	1311	5/8	US8AT	1044372	17.5	1047383	4.3
MB20T200	1036234*	-	20	298	3/4	US8AT	1044381	17.5	1047392	4.8
MB20T350	1036243*	-	20	456	7/8	US8T	1044404	20.8	1047425	7.6
MB20T650	1036252*	-	20	753	1	US8T	1044417	20.8	1047431	8.6
MB20T1150	1036261*	-	20	1311	1-1/8	US10T	1044426	46.5	1047440	12.5
MB25T350	1036270*	-	25	533	1-1/4	US10T	1044435	46.5	1047459	15.0
MB25T650	1036279*	-	25	865						
MB25T1150	1036288*	-	25	1421						
MB30T650	1036297*	-	30	865						
MB30T1150	1036306*	-	30	1421						

* Hook is New S-320N style. Replacement latch kit is S-4320. PL latch and S-4055 latch will not fit.



UB500 Non Swiveling Overhaul Ball



**S320 or S320N
Eye Hook**



**S316A SHUR-LOC®
Eye hook**

- Each ball can be equipped with the new McKissick® US422T Wedge & Socket which can be easily adjusted to fit various sizes of wire rope by changing the wedge (Ensure that the correct wedge is used for selected wire rope size).
- All hooks used on UB500 Overhaul Balls (S320, S320N & S316A) are forged from alloy steel. The S320 and S320N hooks come complete with latches.
- Design Factor 4:1.
- Sizes 4 tons through 10 tons available with Crosby's S1316A "Positive Locking" SHUR-LOC® hook which may be used for lifting personnel. Meets OSHA Rule 1926.550 (g).
- The S320 hook (PL latch) and the S320N hook (S4320 latch), with the proper latch attached, may be used for personnel lifting when secured with proper device (Bolt, nut and pin for the PL latch; Cotter pin for the S4320 latch). Meets OSHA Rule 1926.550(g).

Overhaul Assembly					Optional US-422T/ US-422 Wedge Socket					
McKissick UB500 Model No.	UB500 "E" Eye Hook Stock No.	UB500 "S" SHUR-LOC Stock No.	Working Load Limit (tons)	Weight Each (lbs.)	Wire Rope Size (In.)	Model No.	Wedge Socket Assy. Stock No.	Weight Each (lbs.)	Wedge Only Stock No.	Weight Each (lbs.)
MB4NS35	1036402*	1036407	4	54						
MB4NS85	1036411*	1036416	4	98	3/8	US4T	1044300	4.6	1047310	0.6
MB4NS150	1036420*	1036425	4	158	7/16	US4T	1044309	4.6	1047301	0.6
MB4NS200	1036429*	1036434	4	200	1/2	US4T	1044318	4.6	1047329	0.6
MS7NS85	1036438*	1036443	7	104	1/2	US5T	1044327	8.5	1047338	1.0
MS7NS150	1036447*	1036452	7	165	9/16	US5T	1044336	8.5	1047347	1.0
MS7NS200	1036456*	1036461	7	205	5/8	US5T	1044345	8.5	1047356	1.0
MS7NS285	1036465*	1036470	7	316	5/8	US6T	1044354	9.4	1047365	1.4
MB10NS150	1036474*	1036479	10	198	3/4	US6T	1044363	9.4	1047374	1.4
MB10NS200	1036483*	1036488	10	242						
MB10NS285	1036492*	1036497	10	347						
MB10NS350	1036501*	1036506	10	385	5/8	US6T	1044354	9.4	1047365	1.4
MB10NS650	1036510*	1036511	10	700	3/4	US6T	1044363	9.4	1047374	1.4
MB10NS150	1036519*	-	12	198	7/8	US8T	1044404	20.8	1047425	7.6
MB10NS200	1036528*	-	12	240	1	US8T	1044417	20.8	1047431	8.6
MB10NS285	1036537*	-	12	347	1-1/8	US10T	1044426	46.5	1047440	12.5
MB12NS350	1036546*	-	12	385	1-1/4	US10T	1044435	46.5	1047459	15.0
MB12NS650	1036555*	-	12	700						
MB12NS200	1036564*	-	15	267	5/8	US8AT	1044372	17.5	1047383	4.3
MB12NS350	1036573*	-	15	425	3/4	US8AT	1044381	17.5	1047392	4.8
MB15NS650	1036582*	-	15	722	7/8	US8T	1044404	20.8	1047425	7.6
MB15NS1150	1036591*	-	15	1280	1	US8T	1044417	20.8	1047431	8.6
					1-1/8	US10T	1044426	46.5	1047440	12.5
					1-1/4	US10T	1044435	46.5	1047459	15.0

* Hook is New S-32N style. Replacement latch kit is S-4320. PL latch and S-4055 latch will not fit.

Split Overhaul Ball

Catalog No.	Stock No.	Wire Rope Size (in.)	Weight Each (lbs.)	A Ball Diameter (in.)
SHB-15	2003822	1/4 - 5/16	15	5.06
SHB-20	2003830	3/8	20	5.38
SHB-50	2003831011	1/2 - 5/8	50	7.12
SHB-100	2003832	5/8 - 3/4 - 7/8	100	9.19

