



# Klein Hand Tools



### Bull-Pin and Bolt Bags

Bolt bag with bull-pin loop on each side. Made of No. 4 canvas with double bottom. 3" (76mm) belt loops or tunnel loop. ALSO AVAILABLE IN LEATHER.

Cat. No.	Description
5416T00000	Canvas, 5"x9"x10" deep (13x23x25 cm). Loops fit belts up to 3" wide (76 MM.). With tunnel loop.



### Standard Side Cutters for Rebar Work

Specially designed and sharpened for cutting soft annealed tie wire used on reinforcing rods. Special, heavy, knurled jaws. Hook bends in one handle for non-slip grip. Coil spring holds jaws open.

Cat. No.	A	B	C	D	E
2017CST000	8-3/4 (222)	1-9/32 (33)	1-5/32 (29)	1/2 (13)	5/8 (16)

With plain handles.



5457T

### Hammer Holder

No. 5457T has tunnel loop to fit belts up to 3-1/2" (89mm) wide or to slide over D-rings, buckles and other accessories.

**MADE OF LEATHER.**

Cat.No.	Nominal Size
5457T00000	4-1/2"x12" (11x30 cm)



5459T

### Erection Wrench Holder

Wrench holders have tool-slots for two erection wrenches. No.5459-T has tunnel loop to fit belts up to 3-1/2" wide (89mm) or to slide over D-rings, buckles and other accessories.

**MADE OF LEATHER.**

Cat. No.	Nominal Size
5459T00000	6"x9-1/2" (15x24 cm)



### Snap Loop

Loop with snap hook for carrying an adjustable wrench, welder's igniter or other tool with hang hole. Slides on belts up to 4" wide (102mm).

**MADE OF LEATHER.**

Cat. No.	Nominal Size
5458000000	1-1/4"x9" (3x23 cm)



**Broad-Head  
Bull Pins**

### Erection Wrenches

Drop-forged from select alloy steel to withstand high-leverage and heavy loads. Extra-heavy-duty head area gives maximum strength and durability. Wrench handle features an extra-deep offset to provide an additional hand-clearance without sacrificing tightening power. Continuous taper of handle make lining-up bolt holes easy, allows use on a range of bolt-hole sizes without binding. Extra-large hub area allows use on larger diameter holes than possible with most other wrenches. Available in heavy, regular and utility nut sizes. Catalog number, bolt size and nominal opening size are stamped on every wrench for easy identification. American Bridge Design.

Cat.No.	Nut Type	Bolt Size	Nominal Opening	Length
3212000000	U.S. Heavy	3/4"	1-1/4"	16-1/2"
3213000000	U.S. Heavy	7/8"	1-7/16"	17-1/4"
3214000000	U.S. Heavy	1"	1-5/8"	17-11/16"



**Extra-Capacity Design**

### Extra Capacity Design

Jaws open 3/16" (4mm) wider than standard wrenches, length for length. Extra capacity allows use of a smaller size wrench to handle bigger jobs. Ideal for use in confined spaces. Same rugged construction as standard design. Chrome plated.

Cat. No.	Length	Capacity
507120000	12"(305mm)	1-1/2" (38mm)

### Broad-Head Bull Pins

A drop-forged, heat-treated bull pin which increases efficiency by providing a larger striking surface. Design of the head also reduces chance of pin slipping from the hand when aligning holes. Angled head and smooth blending of radii increase strength and reduce the danger of chipping. Below the head, squared-off shoulders have been forged to provide a surface for applying wrench to loosen wedged bull pins. Long, even taper reduces binding and hang-up. Klein broad-head bull pins offer added resistance to "mushrooming", permitting much longer use than is possible with conventional designs. Black finish.

**Note: OSHA specifically states that, "impact tools such as drift pins, wedges, and chisels, shall be kept free of mushroomed heads."**

Cat. No.	Top Diameter	Point Diameter	Length
3255000000	1-1/4" (31.8 MM.)	5/16" (7.9 MM.)	13" (330 MM.)
3256000000	1-1/16" (27.0 MM.)	1/4" (6.4 MM.)	10" (254mm)

All dimensions are nominal.



**Adjustable-Head  
Construction Wrench**

### Adjustable-Head Construction Wrench

Versatile wrench fits all nuts and bolts to 1-1/2" (38.1 MM.). Eliminates the need for carrying several fixed-size wrenches. Drop-forged from select alloy steel with continuous-taper handle. Industrial black finish.

Cat. No.	Max. Size Capacity	Length
3239000000	1-1/2"(38.1mm)	15"(381mm)



### Hexagonal Bars

Cat. No.	Hex. Diameter	Length
3242000000	3/4" (19.1mm)	30"(76mm)
3243000000	7/8"(22.2 MM.)	36" (91 cm)